

LEVER LOCK

Operating Instructions

MICO[®]

THIS NOTICE MUST BE AFFIXED
ON DASH IN VIEW OF OPERATOR

⚠ WARNING



**PREVENT
ROLLAWAY**

Read operating instructions before using brake lock.

The Brake Lock is a supplemental safety device. It is not to be used in place of the original equipment parking brake.

Always set parking brake and use wheel chocks and outriggers with Brake Lock.

Release Brake Lock before moving vehicle.

Do not use Brake Lock for overnight or prolonged parking.

Principles of Operation

The MICO[®] Lever Lock is a **SUPPLEMENTAL** safety device and is **NOT** to be used in place of the original equipment parking brake. When used with existing vehicle parking brake, the MICO[®] Lock uses a portion of the vehicle's hydraulic service brake system to provide additional brake holding action.

When the Lever Lock is activated and hydraulic service brakes applied, hydraulic pressure is locked in the service brake system. In this way, the hydraulic service brakes continue to be applied after the operator removes their foot from brake pedal.

The Lever Lock does not increase brake pressure, it only locks in pressure generated by pushing on the brake pedal. The harder the operator pushes on the brake pedal, the higher the pressure in the brake system.

Because the Lever Lock is locking hydraulic brake pressure, any leak in the hydraulic brake system will allow pressure to decrease and release brakes. The hydraulic service brake system must be kept in good operating condition to ensure that pressure locked by the Lever Lock will be maintained.

The MICO[®] Lever Lock has a Low Pressure Warning Switch. This switch is to be used with a visual or audible alarm which will alert operator(s) in or around the vehicle of a possible unsafe reduction in brake system pressure and holding capability.

When the lever of the Lever Lock is moved to the full lock position, alarm will sound, indicating insufficient brake holding pressure. The operator then pushes on the brake pedal until sufficient brake pressure has been reached, causing alarm to stop. If a loss of pressure occurs in the locked brake system, the alarm will sound again indicating insufficient brake holding pressure.

Changes in the outside temperature may cause locked up pressure to increase or decrease. Higher temperatures may cause increased pressure which may cause brake system damage and failure. Lower temperatures may cause decreased pressure which can reduce holding level of brakes. For these reasons, the MICO[®] Lever Lock must not be used for overnight or prolonged parking. To minimize these pressure changes, the Lever Lock must be released and reapplied every hour.

In applications where there is no horn or other audible device on the vehicle, one should be installed. A visual pressure gauge can also be used to indicate to the operator when there is adequate hydraulic pressure locked up or when there has been a pressure loss in the system after lock-up.

ATTENTION

These operating instructions must be placed in cab of vehicle in a place available to operator to ensure proper operation of Lever Lock.

The self-adhesive warning label, accompanying each Lever Lock, must be affixed in cab in view of operator.

MICO is a trademark and registered trademark of MICO, Inc. MICO is registered in the U.S. Patent and Trademark Office as well as in Australia, Canada, Indonesia, Japan, Peoples Republic of China, South Korea, and the European Community.

MICO[®]

MICO, Inc.

1911 Lee Boulevard / North Mankato, MN U.S.A. 56003-2507

Tel: +1 507 625 6426 Fax: +1 507 625 3212

OPERATING INSTRUCTIONS

To activate Lever Lock


1. Bring vehicle to complete stop.
2. Set mechanical parking brake.
3. Remove foot from brake pedal and observe if the vehicle remains stationary.
4. Move lever of MICO® Lock to full lock position as indicated on dash plate (Figure 1). Alarm will start. If alarm does not start, discontinue use of lock, determine cause and correct problem before using lock.
5. Apply service brakes firmly until alarm stops.
6. Use wheel chocks, outriggers and any other means to keep all wheels that are in contact with the ground from moving as required by manufacturer recommendations.

If alarm starts while Lever Lock is in use

This indicates unsafe brake system pressure. Discontinue use of lock, determine cause and correct problem before using lock.

To release Lever Lock

1. Retract outriggers and remove wheel chocks. Remove any other means used to keep all wheels that are in contact with ground from moving.
2. Move lever of MICO® Lock to full release position as indicated on dash plate (Figure 2).
3. Release mechanical parking brake.



INSPECTIONS AND TESTS

Federal regulations require that the parking brakes are capable of holding vehicles on a 20% grade with rated capacity load, until intentionally released.

It is recommended that parking brake and MICO® Lever Lock be tested daily, along with other safety equipment such as lights, horn, etc.

Testing Procedure

1. The vehicle must be fully loaded and driven on a 20% grade.
2. Parking brake and MICO® Lever Lock must be fully applied with engine running and transmission in neutral.
3. To test lever lock, operator must release parking brake, leaving MICO® Lever Lock applied, and remain in driver's seat. Vehicle must remain parked, without movement, for at least one minute.

4. To test parking brake, operator must apply parking brake, release MICO® Lever Lock, and remain in driver's seat. Vehicle must remain parked, without movement.

If vehicle moves while parking brake is applied, parking brake must be inspected and adjusted or replaced and tested again.

If vehicle moves while MICO® Lever Lock is applied, all hydraulic brake fittings, hoses, lines, and wheel cylinders must be inspected for leaks. Fittings which leak must be tightened or replaced. Hoses, lines, or wheel cylinders which leak must be replaced or serviced. Vehicle must be tested again and if it fails to remain parked with MICO® Lever Lock applied, lever lock must be replaced and original lock should be returned to MICO for inspection and tests.

This document is intended to provide general information about MICO Products. MICO, Inc. has attempted to present accurate information about MICO Products in its catalogs, brochures, and other printed materials. MICO, Inc. is not responsible for errors, inaccuracies, or inconsistencies that may exist in any catalog, brochure, or other printed materials or any damages arising from or related to reliance on information in them. Materials and specifications for MICO Products set forth in catalogs, brochures, and other printed materials are subject to change without notice or obligation. Refer to www.mico.com for the most recent versions of our literature. If you have any questions concerning MICO Products, please contact MICO, Inc. All MICO Products and service are sold and provided subject to the MICO Warranty at www.mico.com in effect on the date of sale or supply.